

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



10/552831


(43) International Publication Date  
28 October 2004 (28.10.2004)

PCT

(10) International Publication Number  
WO 2004/093313 A2

- (51) International Patent Classification<sup>7</sup>: H03G 3/30
- (21) International Application Number: PCT/TB2004/001073
- (22) International Filing Date: 22 March 2004 (22.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 03101059.8 17 April 2003 (17.04.2003) EP
- (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LAMBRECHT, Xavier, Jean, Francois [BE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).
- (74) Agent: VOLMER, Georg; Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FRONT-END SENSITIVITY BOOSTER



(57) Abstract: The invention relates to a method for increasing the sensitivity of a chain of amplifiers that comprises the steps of amplifying a signal by means of a first amplifier with a gain factor  $A_1 = A_{1,m} \cdot \Delta A_1$ , where  $A_{1,m}$  denotes a constant gain factor and  $A_1$  denotes a gain factor variation with  $1 \leq A_{1,min} \leq A_1 \leq A_{1,max}$ , further amplifying the signal by means of a second amplifier with a controllable gain factor  $A_2 \leq A_{2,max}$ , where variations  $A_1$  of the gain of the first amplifier are compensated by reducing the gain  $A_2$  of the second amplifier, so that the difference between the chain gain factor  $A_C = A_1 \cdot A_2$  and a target chain gain factor  $A_T \leq A_{T,max}$  becomes zero. To solve the object of the invention to provide a method for increasing the sensitivity of a chain of amplifiers that suffers from gain factor variations, it is proposed that the signal at the output of the second amplifier is additionally fed into a divider that applies a fixed factor  $A_3 \leq 1$  to its input, that variations  $A_1$  of the gain factor  $A_1$  of the first amplifier as well as the fixed factor  $A_3$  are at least partially compensated by the gain factor  $A_2$  of the second amplifier, so that the difference between the chain gain factor  $A_C' = A_1 \cdot A_2 \cdot A_3$  and the target chain gain factor  $A_T$  becomes minimum, and that the fixed factor  $A_3$  is chosen so that there exist at least some combinations of values  $A_1$  and  $A_T$  for which said difference can be forced to zero, and some combinations of values  $A_1$  and  $A_T$ , for which said difference can no longer be forced to zero due to the limitation  $A_2 \leq A_{2,max}$ . The invention further relates to a device for increasing the sensitivity of a chain of amplifiers.